

Fuel systems

Spin-on filter

Product overview - Spin-on filters for diesel fuel

Single Spin-on filters
with or without bleed pump



Type		330VTEB	330VTEPB	340VTEB	340VTEPB	350VTEB	350VTEPB
Max. capacity in l/hr		360	270	620	465	800	600
Version		single	with pump	single	with pump	single	with pump
Connections*		M16 x 1.5*		M16 x 1.5*		M16 x 1.5*	
Dimensions (mm)	Height	205		265		325	
	Width	120		120		120	
	Depth	120		120		120	
Weight (kg)		1.3		1.45		1.6	
Replacement filter	10 µm (standard)	VT33EB		VT34EB		VT35EB	
	30 µm (optional)	VT33ER		VT34ER		VT35ER	
Replacement advice				Minimum annually			
Certification				Fire resistant ISO 10088			



*A connection kit for 10mm hose and three blind plugs is standard supply



Double Spin-on filters
Parallel or in line

Type		75330VTEB	75340VTEB	75350VTEB
Max. capacity in l/hr		360	620	800
When both filters are in use		380	760	920
Version		Double	Double	Double
Connections		R 1/2	R 1/2	R 1/2
Dimensions (mm)	Height	305	365	425
	Width	310	310	310
	Depth	167	167	167
Weight (kg)		4,7	5	5,3
Replacement filter	10 µm (standard)	2 x VT33EB	2 x VT34EB	2 x VT35EB
	30 µm (optional)	2 x VT33ER	2 x VT34ER	2 x VT35ER
Replacement advice		When vacuum gauge indicates between -0.2 and -0.38 kg/cm², or annually		
Certification		Fire resistant ISO 10088		