

VETUS V-CAN

V-CAN connection cables

Available in six different lengths for use with BOW PRO and RIMDRIVE installations.

Type	Description
BPCAB1HF	V-CAN cable 1 m Halogen free
BPCAB5HF	V-CAN cable 5 m Halogen free
BPCAB10HF	V-CAN cable 10 m Halogen free
BPCAB15HF	V-CAN cable 15 m Halogen free
BPCAB20HF	V-CAN cable 20 m Halogen free
BPCAB25HF	V-CAN cable 25 m Halogen free



BPCAB..HF



CANVPS



CANVT



CANVHUB


Type	Description
CANVPS	V-CAN Power supply incl. safety
CANVT	V-CAN Terminating resistor
BPCABCGC	V-CAN Gender changer for joining CAN bus extension cables
CANVHUB	V-CAN bus 3-point hub



BPCABCGC

CANVERTER

The CANverter is a plug-and-play gateway that allows you to combine different CAN (Controller Area Network) protocols.



Type	Description
CANV2N2	CANverter bi directional NMEA2000 to V-CAN
CANV2Y2	CANverter bi directional J1939 to V-CAN
CANV2N1	CANverter mono directional V-CAN to NMEA2000
CANR	CANrepeater
CANVM12A	CANverter M12 adapter cable

Type	Description
CANNS500	Digital Battery Monitoring Shunt NMEA2000 and WiFi connection, max. current 500A
CANNME7	Multifunction Display for Electric Propulsion 7" display, NMEA2000



CANVERTER



CANVM12A



CANNS500



CANNME7