



Accessories

Universal inspection port for fresh water tanks ILT120PL / ILT120PH

Easy access for cleaning and inspection

These innovative VETUS inspection ports are designed for easy access to your fresh water tank. With a reliable clamp-and-seal design, they ensure a watertight fit and can be installed on both thin- and thick-walled tanks. The ILT120PL is suitable for tank walls up to 4 mm. The ILT120PH handles wall thicknesses from 4 to 10 mm, ideal for VETUS ATANK models. Both versions feature a modular design, allowing additional connection kits (such as ILTCOND) to be added for a complete fresh water system upgrade.



ILT120

Specifications

- Universal inspection port for fresh water tanks
- Watertight "clamp and seal" design using silicone gasket
- Suitable for synthetic, G.R.P., or metal tanks
- Quick and simple installation using the VETUS hole saw (VSAW159)
- Compatible with ILTCOND connection kit for tank upgrades
- Robust construction with counter flange and five-bolt locking system

Specification	ILT120PL	ILT120PH
Suitable wall thickness	0,8 - 4 mm	4 - 10 mm
Suitable diameter	120 mm	120 mm
Required hole diameter	159 mm	159 mm
Material	Synthetic, corrosion-proof	Synthetic, corrosion-proof
Compatible with ILTCOND	Yes	Yes
Application	Fresh water, waste water tanks	Fresh water, waste water tanks

ILTCOND - Fresh water connection kit

All-in-one upgrade for your tank inspection port

The VETUS ILTCOND is a complete fresh water connection kit that transforms your ILT inspection port (ILT120PL or ILT120PH) into a fully functional connection hub.

Specifications

- Turns ILT120 inspection ports into a full connection hub
- Includes:
 - Ø 38 mm fresh water fill connection.
 - Ø 13 mm fresh water suction connection
 - Ø 16 mm ventilation connection
- SAE 5-hole pattern for level sensor
- Made from corrosion-resistant materials
- Optional a 38 mm connection elbow 90 degrees (ILTCON90) is available



ILTCOND

Specification	ILTCOND
Compatible with	ILT120PL / ILT120PH
Application	Fresh water tanks

ILTCON90 - 90° elbow adapter

- 90-degree Ø 38 mm connection for ILTCONW
- Ideal for tight spaces



ILTCON90

Type	Description
ILTCON90	Ø 38 mm elbow for ILTCOND

