

Waste water systems

Electric toilet control panels

Control switch for TMWQ + TMSQ toilet

Full control over the flush

A simple and effective two function switch to fill or empty the bowl.

Specifications

- Switch dimensions 78x47 mm
- Build-in depth 40 mm
- Complete installation package including 3 m cable
- Suitable for 12 or 24 VDC
- Waterproof IP65



TMWBS

Control panel for TMWQ + TMSQ toilet

Pre-programmed comfort

The panel is easy to operate with just four functions. It has an eco (± 1,2 L) and normal flush (± 2,2 L) button and a fill or empty bowl button. Using a marine toilet was never this easy, just touch the button!

Specifications

- Panel dimensions 110x110 mm
- Build-in depth 50 mm, hole size Ø 76 mm
- Complete installation package including 3 m cable
- Suitable for 12 or 24 VDC
- Waterproof IP65



TMWBP

Electric marine toilets

SMTO - Ultra compact electric toilet

Specifications

- Quiet electric macerator
- Soft-close and quick-release toilet seat
- Floor mount
- Extra compact size
- Lightweight for easier handling and installation
- 12 V or 24 V DC operation




Incl. with SMTO2



Incl. with SMTO2S

Type	Control type	Voltage (V DC)	Consumption (A)	External Ø discharge (mm)	Water inlet connection	Noise level (dBA)	Weight (kg)
SMTO212	Control panel (included)	12	25	19	Female G ³ / ₄	± 60	17,5
SMTO224	Control panel (included)	24	12,5	19	Female G ³ / ₄	± 60	17,5
SMTOS12	Switch (included)	12	25	19	Female G ³ / ₄	± 60	17,5
SMTOS24	Switch (included)	24	12,5	19	Female G ³ / ₄	± 60	17,5



SMTO

