

Waste water systems

Rigid tanks for waste water

WWS series

Complete system with pump and sensor

The WWS tanks are fully equipped units designed for waste water (black water and grey water). These translucent tanks come complete with an EMP140 pump, level sensor, inspection cover, and fittings. Only the level gauge and inlet fitting need to be ordered separately. All connections are located at the top to avoid leaks. All versions come with an opening for the inlet fitting (RT..B sold separately). The tank can be emptied using the pump or from the shore via the extraction pipe.


Specifications

- Available in 42, 61, 88, and 120 L
- Includes 12 V or 24 V waste water pump
- Odour-proof translucent high-quality polyethylene
- Ready-to-use: All major components pre-installed
- Easy to maintain: Top-mounted access and connections
- Complies with the ISO 8099 standard




Type	Capacity (L)	Pressure max. (bar)	Wall thickness (mm)	Connections breather Ø (mm)	Connections suction Ø (mm)	Connections pump (mm)	Colour
WWS4212B	42	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS4224B	42	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS6112B	61	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS6124B	61	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS8812B	88	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS8824B	88	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS12012B	120	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent
WWS12024B	120	0,3	6,5	Angled, rotating 19	Angled, rotating 38	Angled, rotating 38	Light grey translucent


Type	Pump Voltage (VDC)	Pump Current (A)	Capacity, at 0 m head (L/min)	Max. suction height (m)	Max. head (m)	Weight (kg)
WWS4212B	12	6	27	3	5	12,5
WWS4224B	24	4	27	3	5	12,5
WWS6112B	12	6	27	3	5	14
WWS6124B	24	4	27	3	5	14
WWS8812B	12	6	27	3	5	16
WWS8824B	24	4	27	3	5	16
WWS12012B	12	6	27	3	5	18
WWS12024B	24	4	27	3	5	18




42 L



61 L



88 L



120 L

Height dimensions includes connectors