



Accessories for waste water tanks

Angled fittings

Synthetic fittings for VETUS flexible tanks (type FT) or rigid tanks (type RT). Suitable for hoses with an internal diameter of Ø 13, 16, 19, 25 or 38 mm. The required hole size for flexible tank is Ø 42 mm and for rigid tanks Ø 43 mm.



Type	Hose Ø (mm)	Angle
RT13B	13	right angle
RT16B	16	right angle
RT19B	19	right angle
RT25B	25	right angle
RT38B	38	right angle

Type	Hose Ø (mm)	Angle
FT13B	13	right angle
FT16B	16	right angle
FT19B	19	right angle
FT25B	25	right angle
FT38B	38	right angle

Anti-siphoning air vent

For more information and available types see page 127.



Universal inspection port for waste water tanks ILT120PL / ILT120PH

Easy access for cleaning and inspection

These innovative VETUS inspection ports are designed for easy access to your waste water tank. With a reliable clamp-and-seal design, they ensure a watertight fit and can be installed on both thin- and thick-walled tanks. The ILT120PL is suitable for tank walls up to 4 mm. The ILT120PH handles wall thicknesses from 4 to 10 mm, ideal for VETUS ATANK models. Both versions feature a modular design, allowing additional connection kits (such as ILTCONW) to be added for a complete waste water system upgrade.



Specifications

- Universal inspection port for waste water tanks
- Watertight "clamp and seal" design using silicone gasket
- Suitable for synthetic, G.R.P., or metal tanks
- Quick and simple installation using the VETUS hole saw (VSAW159)

- Compatible with ILTCONW connection kit for tank upgrades
- Robust construction with counter flange and five-bolt locking system

Specification	ILT120PL	ILT120PH
Suitable wall thickness	0,8 - 4 mm	4 - 10 mm
Suitable diameter	120 mm	120 mm
Required hole diameter	159 mm	159 mm
Material	Synthetic, corrosion-proof	Synthetic, corrosion-proof
Compatible with ILTCONW	Yes	Yes
Application	Waste water, fresh water tanks	Waste water, fresh water tanks

