

# Power on board

## Accessories

### Battery cables type BATC

VETUS battery cables are extremely flexible and have a PVC insulation jacket with a temperature range of -20° to +85°C. Battery cables are available in black for negative and red for positive direct current with a cross sectional area of 6, 10, 35, 50, 70, 95 or 120 mm<sup>2</sup>.

**Note:** Matching battery cable tags should be ordered separately (type BATCC).



Type	Cross sectional area (mm <sup>2</sup> )	Colour
BATC06M	6	Black
BATC10M	10	Black
BATC35	35	Black
BATC50	50	Black
BATC70	70	Black
BATC95	95	Black
BATC120	120	Black

Type	Cross sectional area (mm <sup>2</sup> )	Colour
BATC06RM	6	Red
BATC10RM	10	Red
BATC35R	35	Red
BATC50R	50	Red
BATC70R	70	Red
BATC95R	95	Red
BATC120R	120	Red

### Cable lugs for battery cables type BATCC



Type	For cable cross sections (mm <sup>2</sup> )	Hole	Qty per set
BATCC0606	6	M6	10
BATCC0608	6	M8	10
BATCC0610	6	M10	10
BATCC1006	10	M6	10
BATCC1008	10	M8	10
BATCC1010	10	M10	10
BATCC3506	35	M6	2
BATCC3508	35	M8	2
BATCC3510	35	M10	2
BATCC5006	50	M6	2
BATCC5008	50	M8	2

Type	For cable cross sections (mm <sup>2</sup> )	Hole	Qty per set
BATCC5010	50	M10	2
BATCC7006	70	M6	2
BATCC7008	70	M8	2
BATCC7010	70	M10	2
BATCC9508	95	M8	2
BATCC9510	95	M10	2
BATCC9512	95	M12	2
BATCC1210	120	M10	2
BATCC1212	120	M12	2
BATCC1510	150	M10	2
BATCC1512	150	M12	2

### Battery terminal sets type BATT

Suitable for cables with cross sections of 16 - 35 mm<sup>2</sup> / 50 - 95 mm<sup>2</sup> up to 150 mm<sup>2</sup>. Supplied with a M10 bolt for a cable up to 150 mm<sup>2</sup>. Made of tinned brass with a stainless steel nut and bolt.

Type	Description
BATT1635	Terminal set for cable 16 - 35 mm <sup>2</sup> , set of 2
BATT5095	Terminal set for cable 50 - 95 mm <sup>2</sup> , set of 2
BATT150	Terminal with M10 bolt, for cable up to 150 mm <sup>2</sup> , set of 2

