

## Comfort



SCU

### Slide

Seat slide for direct mounting. The sliding mechanism can be moved through 135 mm in total and locked in one of seven positions.

Type	Height (H) (mm)	Mounting hole pattern	Base	Weight (kg)	Load static (kg)	Load dynamic (kg)
SCU	70	R + S	S	2	204	102



PCR38



PCRS38

### Pedestal, removable (fixed height)

With 360° swivel or slide and recessed anodised base. Base and pedestal fit most commonly used similar systems in the market.

Type	Swivel (hole pattern)	Height (H) (mm)	Post Ø (D2) (mm)	Base Ø (D3) (mm)	Recessed depth (mm)	Cut out deck Ø (mm)
PCR38	Swivel (S)	380	60	229	70	90
PCRS38	Slide (R)	380	60	229	70	90



PCRQ33



PCRQ38


### Pedestal, removable (fixed height)

With 360° swivel and recessed anodised base. Base and pedestal fit most commonly used similar systems in the market. Swivel 3° angled.

Type	Swivel (hole pattern)	Height (H) (mm)	Post Ø (D2) (mm)	Base Ø (D3) (mm)	Recessed depth (mm)	Cut out deck Ø (mm)
PCRQ33	Quick position (S)	330	60	229	70	90
PCRQ38	Quick position (S)	380	60	229	70	90



PCRBASE



### Base, for pedestal

This (spare) plug-in pedestal base can be used as an extra mounting position or as replacement for existing pedestal bases. The base is made of a marine grade anodized aluminium.

Type	Height (mm)	Base Ø (D3) (mm)	Recessed depth (mm)	Cut out deck Ø (mm)
PCRBASE	82	229	70	90