


Marine fittings, brass

Water scoop**




WCAP..

Type	Thread (G)*	ØB (mm)	H (mm)	C (mm)	Q (mm)	ØR (mm)	SW (mm)	U (mm)	V (mm)	Weight (kg)
WCAP1/2	1/2"	15	96	72	49	38	26	91	3	0,3
WCAP3/4	3/4"	19	103	77	58	48	32	105	3	0,5
WCAP1	1"	26	104	76	61	55	38	108	3	0,6
WCAP11/4	1 1/4"	26	104	78	61	55	38	108	3	0,7
WCAP11/2	1 1/2"	39	113	82	72	72	56	134	3	0,9
WCAP2	2"	51	126	91	89	88	68	156	3	1,5
WCAP21/2	2 1/2"	65	155	112	113	113	92	198	5	2,4
WCAP3	3"	77	134	134	129	120	105	238	5	3,9

* According to ISO 228/1-G..B

** For continuous immersion in salt water, we advise **against** the use of brass fittings.

Thru-hull - Chamfered**



DOORB..


Machined surface

Type	Thread (G)*	ØB (mm)	H (mm)	C (mm)	ØQ (mm)	ØR (mm)	SW (mm)	Weight (kg)
DOORB3/8	3/8"	11	58	53	34	36	22	0,20
DOORB1/2	1/2"	15	64	58	40	39	25	0,25
DOORB3/4	3/4"	19	72	66	49	49	32	0,25
DOORB1	1"	25	77	70	56	56	40	0,35
DOORB11/4	1 1/4"	34	83	76	65	66	50	0,45
DOORB11/2	1 1/2"	39	84	78	72	72	56	0,60
DOORB2	2"	50	102	94	84	84	68	0,90
DOORB21/2	2 1/2"	65	132	123	110	111	91	1,70
DOORB3	3"	76	150	140	127	124	105	2,50

* According to ISO 228/1-G..B

** For continuous immersion in salt water, we advise **against** the use of brass fittings.

Hose connector 90°**



HPM..B

Type	Thread (G)*	ØU (mm)	ØB (mm)	H (mm)	C (mm)	SW (mm)	L (mm)	Weight (kg)
HPM1/2B	1/2"	13	8	37	15	25	48	0,08
HPM3/4B	3/4"	19	12	47	16	30	50	0,15
HPM1B	1"	25	19	58	20	37	58	0,26
HPM11/4B	1 1/4"	32	24	67	20	50	70	0,45
HPM11/2B	1 1/2"	38	29	70	21	55	77	0,57

* According to ISO 228/1-G..B

** For continuous immersion in salt water, we advise **against** the use of brass fittings.