

Around the engine

Mechanical engine remote controls

All remote controls (except type AFST) have a neutral safety switch as standard, which prevents the engine from being started when the gearbox is engaged. Controls are supplied with a red and a black knob.

Type SISCO - single lever

With stainless steel (AISI 316) high-gloss polished handle and housing

VETUS single lever remote control for side mounting. The push-pull cables can be installed horizontally or vertically.

Type	Length (mm)	Width (mm)	Height (mm)	Handle length from centre (mm)	Mechanism depth from centre (mm)
SISCO	142	122	85	200	243
SISCOG	142	122	85	200	243



Type SICO - single lever

With stainless steel (AISI 316) high-gloss polished handle and synthetic housing

VETUS single lever remote control for side mounting.

Type	Length (mm)	Width (mm)	Height (mm)	Handle length from centre (mm)	Mechanism depth from centre (mm)
SICO	147	127	85	200	243
SICOG	147	127	85	200	243



Type RCTOPS - single lever

With high-gloss polished stainless steel (AISI 316) handle and housing

VETUS single lever remote control for top mounting.

Type	Length (mm)	Width (mm)	Height (mm)	Handle length from centre (mm)	Mechanism depth (mm)
RCTOPS	162	104	237	200	208
RCTOPSG	162	104	237	200	208



Type RCTOPTS - twin lever

With high-gloss polished stainless steel (AISI 316) handles and housing

VETUS twin lever remote control for top mounting.

Type	Length (mm)	Width (mm)	Height (mm)	Handle length from centre (mm)	Mechanism depth (mm)
RCTOPTS	162	200	237	200	208
RCTOPTSG	162	200	237	200	208

