

Pumps


BLPM020

BLP..

BLSWITCH

BLPS..

Manual membrane pump

A high quality membrane pump suitable for pumping/ transferring bilge water, seawater or diesel.

- Synthetic housing, metallic parts of stainless steel (AISI 316)
- Easy to remove clamping ring for maintenance and or head rotation
- Horizontal or vertical mounting
- Self-priming

Suitable for boats up to 12 m (ISO 15083).

For all suitable hoses see page 466 of the catalogue.

Type	Suction lift (m)	Discharge head (m)	Capacity L/stroke	Hose connection Ø (mm)	Advised hose type
BLPM020	3	4	0,44	32	DWHOSE32B

Bilge pump

Submersible bilge pumps (IP67). Detachable strainer acts as screw-down base. Durable snap connection for easy cleaning. Double seals for long lifetime. Internal components are made from stainless steel (AISI 316). Comes with 1.2 m cable. For all suitable hoses see page 466 of the catalogue.

Type	Voltage (DC)	Current A @ 13,6 V	Capacity L/min @ 0 m	Max. head (m)	Dimensions Ø x H (mm)	Hose connection Ø (mm)	Advised hose type
BLP12500	12	3	40	4	90 x 120	19	DWHOSE19B
BLP121000	12	3	50	4	90 x 120	28,5	DWHOSE28B
BLP122000	12	6	110	4	120 x 150	28,5	DWHOSE28B
BLP123000	12	9	160	5	130 x 180	32	DWHOSE32B

Type	Voltage (DC)	Current A @ 27,1 V	Capacity L/min @ 0 m	Max. head (m)	Dimensions Ø x H (mm)	Hose connection Ø (mm)	Advised hose type
BLP24500	24	1,5	40	4	90 x 120	19	DWHOSE19B
BLP242000	24	3	111	4	120 x 150	28,5	DWHOSE28B
BLP243000	24	4,5	147	5	130 x 180	32	DWHOSE32B

Level switch

This switch activates the pump when the bilge water level reaches 50 mm.

- Made from high quality synthetic material
- Suitable for 12 and 24 VDC
- Suitable for fresh and salt water
- Comes with 1 m cable

Type	Voltage (DC)	Max. current (A)	Total width (mm)	Total length (mm)	Cable length (m)
BLSWITCH	12 / 24	15	70	117	1

Stirrup type pump

Sturdy single action plunger pump suitable for fresh water, seawater or other fluids normally present in the bilge.

- Material: durable synthetic (PP)
- Temperature resistant to max. 60° Celsius
- Ergonomically shaped handle
- Self priming
- Hose length: 980 mm

Type	Hose connection Ø (mm)	Stroke length (mm)	Capacity L/stroke
BLPS04	26,5	280	0,4
BLPS07	26,5	530	0,7